



weitere Abmessungen auf Anfrage | further dimensions on request

zusätzliche Oberflächenqualitäten analog Seite | additional surface qualities analog page 58

DIN	Abmessung dimension	A	B	C	MB 1.4435	e-pol. 1.4435	E	C	MB 1.4404	C	MB 1.4404
DN004*	6.0 x 1.0	6.0	4.0	28.6	708103	710952	Ø 25.0	XXX	XXX	XXX	XXX
DN004*	6.0 x 1.0	6.0	4.0	28.6	704208	710953	Ø 34.0	XXX	XXX	XXX	XXX
DN006	8.0 x 1.0	8.0	6.0	28.6	706001	710954	Ø 25.0	28.6	**	12.7	**
DN006*	8.0 x 1.0	8.0	6.0	28.6	703087	710955	Ø 34.0	XXX	XXX	XXX	XXX
DN008	10.0 x 1.0	10.0	8.0	28.6	703248	710956	Ø 25.0	28.6	**	12.7	**
DN008*	10.0 x 1.0	10.0	8.0	28.6	702970	710957	Ø 34.0	XXX	XXX	XXX	XXX
DN010*	12.0 x 1.0	12.0	10.0	28.6	706740	708997	Ø 25.0	XXX	XXX	XXX	XXX
DN010*	12.0 x 1.0	12.0	10.0	35.0	701776	707211	Ø 34.0	28.6	706479	18.0	700871
DN010*	12.0 x 1.0	12.0	10.0	36.0	702476	710958	Ø 50.5	XXX	XXX	XXX	XXX
DN010*	13.0 x 1.5	13.0	10.0	28.6	707990	707991	Ø 25.0	XXX	XXX	XXX	XXX
DN010	13.0 x 1.5	13.0	10.0	28.6	703938	707549	Ø 34.0	28.6	706480	18.0	705455
DN010*	13.0 x 1.5	13.0	10.0	36.0	703888	709283	Ø 50.5	XXX	XXX	XXX	XXX
DN015*	19.0 x 1.5	19.0	16.0	28.6	708930	708931	Ø 25.0	XXX	XXX	XXX	XXX
DN015	19.0 x 1.5	19.0	16.0	28.6	702457	707213	Ø 34.0	28.6	706481	18.0	700872
DN015*	19.0 x 1.5	19.0	16.0	36.0	701593	709179	Ø 50.5	XXX	XXX	XXX	XXX
DN020	23.0 x 1.5	23.0	20.0	28.6	702458	708723	Ø 34.0	28.6	706482	18.0	700873
DN020*	23.0 x 1.5	23.0	20.0	36.0	701594	710959	Ø 50.5	XXX	XXX	XXX	XXX
DN025	29.0 x 1.5	29.0	26.0	36.0	701786	707212	Ø 50.5	28.6*	706483	21.5	700874
DN032	35.0 x 1.5	35.0	32.0	36.0	700865	704084	Ø 50.5	28.6*	706484	21.5	700875
DN040	41.0 x 1.5	41.0	38.0	36.0	702477	708724	Ø 50.5	28.6*	706485	21.5	700876
DN050	53.0 x 1.5	53.0	50.0	36.0	700867	707214	Ø 64.0	28.6*	706486	21.5	700877
DN065	70.0 x 2.0	70.0	66.0	48.0	700868	709084	Ø 91.0	48.0	**	28.0	700878
DN080	85.0 x 2.0	85.0	81.0	48.0	700869	709085	Ø 106.0	48.0	**	28.0	700879
DN100	104.0 x 2.0	104.0	100.0	48.0	700870	710960	Ø 119.0	48.0	**	28.0	700880
DN125	129.0 x 2.0	129.0	125.0	66.0	706088	710961	Ø 155.0	66.0	**	28.0	703479
DN150	154.0 x 2.0	154.0	150.0	66.0	706089	710962	Ø 183.0	66.0	**	28.0	703553
DN200	204.0 x 2.0	204.0	200.0	66.0	706090	710963	Ø 233.5	66.0	**	28.0	704460

\*) nicht in der DIN-Norm enthalten | non-standard

\*\*) auf Anfrage | on request

ISO	Abmessung dimension	A	B	C	MB 1.4435	e-pol. 1.4435	E	C	MB 1.4404	C	MB 1.4404
DN008	13.5 x 1.6	13.5	10.3	28.6	707311	708244	Ø 25.0	28.6	706329	12.7	710966
DN008*	13.5 x 1.6	13.5	10.3	28.6	708793	709675	Ø 34.0	28.6	706488	18.0	703127
DN008*	13.5 x 1.6	13.5	10.3	36.0	702482	710967	Ø 50.5	XXX	XXX	XXX	XXX
DN010	17.2 x 1.6	17.2	14.0	28.6	707312	709473	Ø 25.0	28.6	706330	12.7	709454
DN010*	17.2 x 1.6	17.2	14.0	28.6	708794	710968	Ø 34.0	28.6	706489	18.0	700921
DN010*	17.2 x 1.6	17.2	14.0	36.0	702565	710969	Ø 50.5	28.6	701596	18.0	710970
DN015*	21.3 x 1.6	21.3	18.1	28.6	708795	710971	Ø 34.0	28.6	706490	18.0	700922
DN015	21.3 x 1.6	21.3	18.1	36.0	701597	708820	Ø 50.5	28.6*	706487	21.5	706333
DN020	26.9 x 1.6	26.9	23.7	36.0	700913	708069	Ø 50.5	28.6*	706491	21.5	700923
DN025	33.7 x 2.0	33.7	29.7	36.0	700914	708212	Ø 50.5	28.6*	706492	21.5	700924
DN032*	42.4 x 2.0	42.4	38.4	36.0	700915	708056	Ø 50.5	28.6	708725	21.5	700925
DN032	42.4 x 2.0	42.4	38.4	36.0	704266	709419	Ø 64.0	28.6*	706493	21.5	710972



## 2.7.2 Clampstutzen DIN 32676

zusätzliche Oberflächenqualitäten analog Seite | additional surface qualities analog page 58

TC/ferrule

ISO	Abmessung dimension	A	B	C	MB 1.4435	e-pol. 1.4435	E	C	MB 1.4404	C	MB 1.4404
DN040	48.3 x 2.0	48.3	44.3	36.0	702475	709045	Ø 64.0	28.6*	706494	21.5	700926
DN050	60.3 x 2.0	60.3	56.3	36.0	700917	709046	Ø 77.5	36.0	710973	28.0	700927
DN065	76.1 x 2.0	76.1	72.1	48.0	700918	709761	Ø 91.0	48.0	710983	28.0	700928
DN080	88.9 x 2.3	88.9	84.3	48.0	700919	710978	Ø 106.0	48.0	710984	28.0	700929
DN100	114.3 x 2.3	114.3	109.7	48.0	700920	710979	Ø 130.0	48.0	710985	28.0	700930
DN125	139.7 x 2.6	139.7	134.5	66.0	710974	710980	Ø 155.0	66.0	710986	28.0	710989
DN150	168.3 x 2.6	168.3	163.1	66.0	710975	710981	Ø 183.0	66.0	710987	28.0	710990
DN200	219.1 x 2.6	219.1	213.9	66.0	710976	710982	Ø 233.5	66.0	710988	28.0	709574

ASME BPE	Abmessung dimension	A	B	C	MB 1.4435	e-pol. 1.4435	E	C	MB 1.4404	C	MB 1.4404
DN ¼"	6.35 x 0.89	6.35	4.57	28.6	706038	710992	Ø 25.0	28.6	710998	12.7	711005
DN ⅜"	9.53 x 0.89	9.53	7.75	28.6	709487	710993	Ø 25.0	28.6	710999	12.7	711006
DN ½"	12.7 x 1.65	12.7	9.4	28.6	708291	709246	Ø 25.0	28.6	706676	12.7	706766
DN ¾"	19.05 x 1.65	19.05	15.75	28.6	708292	709150	Ø 25.0	28.6	708686	12.7	706767
DN 1"	25.4 x 1.65	25.4	22.1	36.0	703969	708043	Ø 50.5	28.6*	706677	21.5	701601
DN 1½"	38.1 x 1.65	38.1	34.8	36.0	702560	709081	Ø 50.5	28.6*	701602	21.5	704001
DN 2"	50.8 x 1.65	50.8	47.5	36.0	702561	709464	Ø 64.0	36.0	711000	28.0*	706678
DN 2½"	63.5 x 1.65	63.5	60.2	36.0	704258	710994	Ø 77.5	36.0	711001	28.0	704380
DN 3"	76.2 x 1.65	76.2	72.9	48.0	704537	710995	Ø 91.0	48.0	711002	28.0	704602
DN 4"	101.6 x 2.11	101.6	97.38	48.0	704538	710996	Ø 119.0	48.0	711003	28.0	704632
DN 6"	152.4 x 2.77	152.4	146.86	66.0	710991	710997	Ø 167.0	66.0	711004	19.1*	708885

\*) nicht in der DIN-Norm enthalten | non-standard



Weitere Varianten wie z.B. Clampstutzen mit Tülle, Clampadapter oder Clampstutzen mit Außen-, bzw. Innengewinde sind ab Lager lieferbar.

Further variants like clamp hose nozzles or (threaded) adapters are consignable from stock.